V&V Summary Report L2 ASCDS Version: 8.4.3

Observation 12707 - L2 Version 2 Chandra X-Ray Center

L2 Processing Date: Feb 8 2012

See axaff12707N002_VV001_vvref2.pdf for the full report

V&V Scientist	Jen Lauer
V&V Date (YYYY-MM-DD)	2012.02.10
V&V Edition	1
V&V Disposition and Status	OK
V&V Charge Time	3.0978000204563

Comments

The data for this observation have been processed using the 'EDSER' sub-pixel event-repositioning algorithm of Li et al. (2004, ApJ, 610, 1204). Small-scale features should become sharper for sources near the aim point. The improvement will be less noticeable for off-axis sources where the size of the point-spread function is comparable to or larger than the size of an ACIS pixel. To take full advantage of the improvement, images should be binned on spatial scales smaller than the size of an ACIS pixel. Note that, at present, the point-spread function has not been calibrated for data to which the EDSER algorithm has been applied. If dither was disabled for the observation, then the algorithm can introduce artificial aliasing effects on spatial scales smaller than a pixel. If you would prefer to use no sub-pixel adjustment or to apply a coordinate randomization, then use acis_process_events to reprocess the data with the parameter pix_adj=NONE or RANDOMIZE, respectively.

,
et RA [deg]
et Dec [deg]
ta
S

